

FDA COMPLIANT MATERIALS PUMPS PF, TT, HVDP, & AP SERIES

FDA-compliant (non-sanitary) drum and centrifugal pumps are specifically constructed of materials safe for food, beverage, pharmaceutical and cosmetic processes where 3A or USDA standards are not required.





FDA Compliant PF Series

- High Performance Solutions

- Available models PFS-B & PFS-BTC with buna o-rings and PFS-P with Perlast o-rings
- Length: 27" (69 cm), 40" (102 cm), 48" (122 cm), 60" (152 cm), & 72" (183 cm)
- Available Motors: Open, TEFC, Explosion Proof, Air
- Tube Diameter: 2" (5.1 cm)
- Discharge: 1" (2.54 cm) hose barb (PFS-B) or welded Tri-Clamp Connection (PFS-BTC)
- Maximum Viscosity: up to 2,000 cps
- Maximum Discharge: 80 ft (24 m)
- Maximum Flow: 40 gpm (151 lpm)
- Maximum Specific Gravity: up to 1.8
- Temperature Range: -20° F (-29° C) to 220° F (105° C)



FDA Compliant TT Series

- Medium Viscosity Solutions

- Available model STTS with Fluorosint seal
- Length: 40" (102 cm)
- Available Motors: Open, TEFC, Explosion Proof, Air
- Tube Diameter: 1-1/2" (3.8 cm)
- Discharge: 1" (2.54 cm) hose barb (STTS) or welded Tri-Clamp Connection (STTS-TC)
- Maximum Viscosity: up to 2,000 cps
- Maximum Discharge: over 30 ft (9 m)
- Maximum Flow: 16 gpm (61 lpm)
- Maximum Specific Gravity: up to 1.8
- Temperature Range: -10° F (-23° C) to 150° F (66° C)







Common Applications:

Food

- Soy sauce
- · Caramel color
- Barbeque sauce
- Plant oils
- Fruit juice
- Milk
- Vinegar
- Wine
- Juice concentrate
- Corn syrup
- Honey
- Molasses
- Spirits
- Diced tomatoes
- Ketchup
- Gravy
- Mustard
- Fruit pieces in liquid

Personal Care & Pharmaceutical

- Bath gels
- Liquid soaps
- Shampoo
- Glycerin
- Hand cream
- Suntan lotion
- Ointments
- Aloe Vera gel
- Clay facial mask
- Toothpaste
- Propylene glycol
- Glycerin
- Sodium hydroxide
- Fluoride
- Dyes
- Fragrance additive
- Formaldehyde
- Water
- Fish oil

FDA Compliant HVDP Series

- High Viscosity Solutions

- Available models HVDP-HR16, HVDP-LR4, & HVDP-LR5 with buna seal, o-rings and stator
- Length: 27" (69 cm), 40" (102 cm), & 48" (122 cm)
- Available Motors: Open, TEFC, Explosion Proof, Air
- Tube Diameter: 2" (5.1 cm)
- Discharge: 1-1/2" (3.8 cm) or 2" (5.1 cm) hose barb or welded Tri-Clamp Connection
- Maximum Viscosity: up to 100,000 cps
- Maximum Discharge: over 300 ft (91 m)
- Maximum Flow: HR 9 gpm (32 lpm)
 LR 7 gpm (27 lpm)
- Maximum Specific Gravity: up to 1.8
- Temperature Range: -20° F (-29° C) to 180° F (82° C)



FDA Compliant AP Series

- Closed System Solutions

- Models AC4, 5, 6, & 8 with buna seal and o-ring
- Electro-polish finish
- NPT & BSP threaded connections standard; welded flanges and tri-clamp connections available upon request
- NEMA or IEC motor adapter frames
- ATEX Certified
- Port Size: <u>AC4</u> 3/4" x 1/2" (1.91 cm x 1.27 cm)
 - AC5 1-1/4" x 3/4" (3.18 cm x 1.91 cm) 1-1/2" x 1-1/4" (3.81 cm x 3.18 cm) 2" x 1-1/2" (5.08 cm x 3.81 cm) 1/2" x 1/4" (1.27 cm x 0.64 cm)
 - <u>AC6</u> 1-1/2" x 1-1/4" (3.81 cm x 3.18 cm) 2" x 1-1/2" (5.08 cm x 3.81 cm) 1-1/4" x 3/4" (3.18 cm x 1.91 cm)
 - AC8 1-1/2" x 1-1/4" (3.81 cm x 3.18 cm) 2" x 1-1/2" (5.08 cm x 3.81 cm) 1-1/4" x 3/4" (3.18 cm x 1.91 cm)
- Maximum Viscosity: up to 300 cps
- Maximum Discharge: up to 89 ft (91 m)
- Maximum Flow: up to 145 gpm (33 m³/h)
- Maximum Specific Gravity: up to 1.8
- Temperature Range: -40° F (-40° C) to 300° F (149° C)







