



First choice when
quality counts.

Husky Twistork Agitator Pump System

- **Gentle “whipfree” mixing action reduces degradation and splashing**
- **Stainless steel with acetal or polypropylene construction pump**
- **Integral system simplifies installation by eliminating messy hose and fitting connections**
- **Quiet, versatile pump connected to agitator lifts solids from bottom of tank and mixes while maintaining suspension**
- **Recommended for viscosities up to 1000 cps***

**Simultaneous
mixing and
evacuating
speeds up your
production line!**

Graco combined two successful technologies to create a new package: the high performance Husky 715 diaphragm transfer/supply pump and the powerful new Twistork bung-mounted agitator/mixer.

This closed system prevents evaporation, reducing VOC emissions. This maintains the purity of the material in the drum and simplifies drum agitation and transfer for improved efficiency and quality.

Typical Fluids Handled

- Mixes most paints, resins, urethanes, epoxies and latex materials – excellent for viscosities to 1000 cps
- Husky 715 available in polypropylene/Teflon® and acetal/Teflon combinations for a wide range of fluids

Typical Applications

- Drum agitation and evacuation
- Tint or dye agitation and supply
- Chemical agitation and transfer
- Thixotropic material agitation and transfer

** Mixing effectiveness and pump flow rate are significantly impacted by fluid viscosity.*

Teflon® is a registered trademark of Du Pont.

Form No. 305-771-E



Technical Specifications

Max. working pressure 7 bar
Air pressure operating range 1,75-7 bar
Max. siphon flow rate
 with 100 cps material 45,4 l/min
 with 1000 cps material 4,54 l/min
Air inlet quick-coupler, nipple (pin)
Fluid outlet 3/4 npt(f)
Max. recommended agitator speed 800 rpm
Agitator air consumption
 at 400 rpm 0,07 m³/min
 at 800 rpm 0,16 m³/min
Pump air consumption
 at 45,4 l/min approx. 0,34 m³/min
Dimensions 1549 mm H x 224 mm W x 290 mm D
Instruction manual 308-656

Accessories

222-011 Grounding Clamp
236-984 Strainer Inlet Kit

Repair Kits

D06-911 Husky Polypropylene/Teflon® Pump Repair Kit
D06-211 Husky Acetal/Teflon Pump Repair Kit
224-820 Pump Air Valve Replacement
207-335 Twistork Motor Repair Kit
236-762 Shaft Seal Repair Kit

Teflon® is a registered trademark of Du Pont.

Ordering Information

238-859 Twistork with Polypropylene/Teflon Pump
238-860 Twistork with Acetal/Teflon Pump

*Graco is registered to I.S. EN ISO 9001.
Any and all specifications contained herein are subject
to change without notice.*



GRACO N.V.
Slakweidestraat 31
B-3630 Maasmechelen - BELGIUM
Tel: (32) 89 770 700 - Fax: (32) 89 770 777

