

# PM 12 VDC Metering Dosing Pump

Constant flow regulation. Pump head in Polypropylene or PVDF and seals in FPM or EPDM.



- Led power on
- Display LCD
- Led Alarm
- Led pulse solenoid
- Flow rate digital adjustment by keys
- Start/Stop key
- Plastic case, protection degree IP65

Model	Pressure max (bar)	Flow rate max (l/h)	Frequency max (imp/min)	ml / pulses	Max suction high (mt)	Standard power supply (*)	Weight (kg)
PM 05-05 12VDC	5	5	120	0,69	1,5	12 VDC	2,3
PM 05-05 12VDC	7	2		0,27			

<b>Pump head</b>	Polypropylene (on request: PVDF, PVC, SS316)
<b>Diaphragm</b>	PTFE
<b>Connections</b>	Polypropylene or PVDF
<b>Foot filter</b>	Polypropylene or PVDF
<b>Injection valve</b>	Polypropylene or PVDF
<b>Suction tube</b>	PVC crystal
<b>Delivery tube</b>	Polyethylene
<b>Standard valves</b>	Ceramic ball
<b>Seals</b>	FPM (on request: EPDM)
<b>Level connection</b>	On request (version KL)
<b>Assembly</b>	Wall-mounting or on horizontal bracket (option)
<b>Consumption</b>	1A

Dimensions  
(mm)

